

IEC 60318-5

43AB

1/2" 2cc

GRAS



Connection: 200 V/LEMO
Volume: 2 cc
Dyn range: 25 dB(A) to 164 dB
ANSI: S3.7 Type 2
IEC: 60318-5

GRAS 43AB

The GRAS 43AB Artificial Ear is a complete test jig for acoustical measurements of hearing aids in accordance with IEC 60318-5 (60126) and ANSI S3.7-1995 on insert type hearing aids in accordance with:

- IEC 60318-5 (60126) reference coupler for the measurement of hearing aids using earphones coupled to the ear by means of ear inserts.
- ANSI S3.7-1995 American National Standard for Coupler Calibration of Earphones.

The 43AB comprises:

- IEC 60318-5 (60126) 2-cm³ Coupler [GRAS RA0038](#)
- [GRAS 40AG ½" Pressure Microphone](#)
- GRAS 26AC ¼" Preamplifier
- [GRAS RA0052 Test Jig](#)
- Studs and moulds for BTE and ITE instruments

The Test Jig has an adjustable spring-loaded arm to exert a variable force on the test object.



Theoretical dynamic range lower limit with GRAS preamplifier	dB(A)	25
Theoretical dynamic range upper limit with GRAS preamplifier @ +120 V / ±60 V power supply	dB	164
Set sensitivity @ 250 Hz (±2 dB)	mV/Pa	12
Set sensitivity @ 250 Hz (±2 dB)	dB re 1V/Pa	-38.5
Coupler volume	mm ³	0.4 ccm
Temperature range, operation	°C / °F	- 30 to 60 / -22 to 140
Temperature coefficient @250 Hz	dB/°C / dB/°F	-0.01 / - 0.006
Humidity range non condensing	% RH	0 to 80
ANSI standard		S3.7 Type 2 (HA-1, HA-2)
IEC standard		60318-5 (former 60126)
ITU-T recommendations		P.380
CE/RoHS compliant/WEEE registered		Yes/Yes/Yes
Connector type		3 m 7-pin LEMO
Weight	g / oz	1.55 / 54.675

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.

Included

GRAS RA0038	IEC 126 2 cc Coupler
	Tube adapters
GRAS 40AG	½" Pressure Microphone, Wide Frequency
GRAS 26AC	¼" Preamplifier
GRAS RA0052	Test Jig

Optional

GRAS 12AK	Power Module
GRAS 42AA	Pistonphone

Miscellaneous

GRAS RA0196	High-tension springs (set of two)
-----------------------------	-----------------------------------

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.

GRAS Worldwide

Subsidiaries and distributors in more
than 40 countries

HEAD OFFICE, DENMARK
GRAS SOUND & VIBRATION
Skovlytoften 33
2840 Holte
Denmark
Tel: +45 4566 4046
www.GRASacoustics.com
gras@grasacoustics.com

USA
GRAS SOUND & VIBRATION
9290 SW Nimbus Avenue
Beaverton, OR 97008
Tel: 503-627-0832
Toll Free: 800-231-7350
www.GRASacoustics.com
sales-usa@grasacoustics.com

UK
GRAS SOUND & VIBRATION
Unit 115, Gibson House,
Ermine Business Park, Huntingdon,
Cambridgeshire, PE29 6XU
Tel: +44 (0) 7762 584 202
www.GRASacoustics.com
sales-uk@grasacoustics.com

CHINA
GRAS SOUND & VIBRATION
Room 315, RuiBo Center(T1)
Lane683, Shenhong Rd,
Minhang District,
Shanghai, China, 201107
Tel: +86 21 64203370
www.GRASacoustics.cn
cnsales@grasacoustics.com



About GRAS Sound & Vibration

GRAS is a worldwide leader in the sound and vibration industry. We develop and manufacture state-of-the-art measurement microphones and related equipment for industries where acoustic measuring accuracy and repeatability are of the utmost importance. This includes applications and solutions for customers within the fields of aerospace, automotive, audiology, consumer electronics and other highly demanding industries. GRAS microphones are designed to live up to the high quality, durability and accuracy that our customers have come to expect, trust and require.

GRAS Sound & Vibration is represented through subsidiaries and distributors in more than 40 countries and is part of Axiometrix Solutions, a leading test solutions provider comprised of globally recognized measurement brands. Read more at www.grasacoustics.com

grasacoustics.com

GRAS
An Axiometrix Solutions Brand