

GRAS 44AA

嘴模拟器，符合ITU-T Rec.P51 内置功率放大器



ITU-T rec.: P.51
Special feature: Built-in power amplifier

GRAS 44AA嘴模拟器是一种近距离模拟人体口腔周围声场的声源，符合IEEE 269 661标准和ITU-T Rec.P51标准 GRAS 44AA 用于测试电话传声器以及通信网络中类似使用的其他传声器。

GRAS 44AA and 44AA-1

At the mouth reference point (MRP), which is 25 mm from the detachable lip ring (35 mm from the mouth of the GRAS 44AA/AA-1), the maximum continuous signal it can produce in $\frac{1}{3}$ -octave bands is 100 dB re. 20 μ Pa in the frequency range of 100 Hz to 16 kHz. Its loudspeaker accepts an external signal either directly or via its own built-in power amplifier (when power is applied).

Jigs are included for calibration according to CCITT P.51 and IEEE 269. These are for use with $\frac{1}{4}$ or $\frac{1}{2}$ microphones. One jig holds the microphone at 0° incidence ($\frac{1}{4}$ only) to the sound source, the other at 90° incidence ($\frac{1}{4}$ or $\frac{1}{2}$).

NOTE: This type of mouth simulator can not be mounted inside a KEMAR head.


ITU-T recommendations		P.51
Connector type		BNC
IEEE standard		269, 661
Input impedance	kΩ	20
Maximum power, continuous	W	10
Maximum power, pulsed 2 sec.	W	50
Temperature range, operation	°C / °F	10 to 35 / 50 to 95
Gain	dB	10
Input signal, max.	Vrms	2
CE/RoHS compliant/WEEE registered		Yes/Yes/Yes
Weight	g / oz	1050 / 37.038

Built-in power amplifier

Maximum continuous output level at MRP [200 Hz - 6 kHz] 110 dB re. 20 μPa

Maximum continuous output level at MRP [100 Hz - 16 kHz] 100 dB re. 20 μPa

Distortion 250 Hz - 8 kHz (Linear signal @ 94 dB at MRP) typically 1%, max. 1.5 %



Frequency response

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.

Included

GRAS RA0104	Jig (CCITT P51)
GRAS RA0105	Jig (IEEE 269)

Optional

GRAS RA0110	Conical mouthpiece
-------------	--------------------

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.

GRAS Worldwide

Subsidiaries and distributors in more than 40 countries

HEAD OFFICE, DENMARK

GRAS SOUND & VIBRATION
Skovlytoften 33
2840 Holte
Denmark
Tel: +45 4566 4046
www.GRASacoustics.com
gras@grasacoustics.com

USA

GRAS SOUND & VIBRATION
9290 SW Nimbus Avenue
Beaverton, OR 97008
Tel: 503-627-0832
Toll Free: 800-231-7350
www.GRASacoustics.com
sales-usa@grasacoustics.com

UK

GRAS SOUND & VIBRATION
Unit 115, Gibson House,
Ermine Business Park, Huntingdon,
Cambridgeshire, PE29 6XU
Tel: +44 (0)7762 584 202
www.GRASacoustics.com
sales-uk@grasacoustics.com

CHINA

GRAS SOUND & VIBRATION
Room 502, Building T1,
No.1398 Ali Center
Shenchang Road,
Minhang District,
Shanghai, China, 201107
Tel: +86 21 400-888-9826
www.GRASacoustics.cn
cnsales@grasacoustics.com



About GRAS Sound & Vibration

GRAS is a worldwide leader in the sound and vibration industry. We develop and manufacture state-of-the-art measurement microphones to industries where acoustic measuring accuracy and repeatability is of utmost importance in R&D, QA and production. This includes applications and solutions for customers within the fields of aerospace, automotive, audiology, and consumer electronics. GRAS microphones are designed to live up to the high quality, durability and accuracy that our customers have come to expect and trust.

GRAS Sound & Vibration is represented through subsidiaries and distributors in more than 40 countries and is part of Axiometrix Solutions, a leading test solutions provider comprised of globally recognized measurement brands. Read more at www.GRASacoustics.com

www.GRASacoustics.com

GRAS
An Axiometrix Solutions Brand