

# GRAS 51AB

Phase Calibrator according to IEC 61043



Freq range: 50 Hz to 6.3 kHz  
ANSI: S1.10  
IEC: 61043

The Sound-intensity Calibrator 51AB is a coupler for phase and level calibrations of sound-intensity microphone pairs. It can be used for residual intensity testing, sound-intensity level calibration and particle velocity calibration as specified in IEC standard 1043 Electroacoustics-Instruments for the measurements of sound intensity- Measurement with pairs of pressure sensing microphones.

## Typical applications and use

- IEC 1043 measurements
- Phase- and level calibration of sound-intensity microphone pairs
- Residual-intensity testing
- Particle-velocity calibration

## Design

The GRAS 51AB can be connected to an external signal generator producing white noise, pink noise or pure tones.

The most important feature of a sound-intensity probe is to be able to measure the real part of a complex sound intensity in highly reactive sound fields as well as in sound fields with a high level of background noise. This ability depends largely on the phase responses of the pair of intensity microphones and, for high-quality pairs, the difference in phase responses must be extremely small.

The phase calibrator consists of a sound source which produces a well defined sound-pressure field simultaneously on both the diaphragms of the measurement microphones. When used for residual intensity testing, the sound pressures present on both diaphragms of the microphones are exactly the same, but with an extremely small phase difference. This phase difference can be expressed as the pressure-intensity index for a given nominal microphone separation.

The IEC standard 61043 states a pressure-intensity index for a nominal microphone separation of 25 mm. With this microphone separation, the phase calibrator has a pressure-intensity Index of more than 27 dB, corresponding to a phase difference of less than 0.006 ° at 100 Hz.

For sound-intensity and particle-velocity calibrations, a phase-shifting element is inserted

between the source and receiving part of the calibrator. This results in a phase shift in sound pressure at one of the microphones; similar to that found in a free field. The result is an output from the microphones similar to what would be obtained if the microphone pair was placed in a free field.

The phase calibrator can be used with 1/2-inch microphones or, by using the included adapters, 1/4-inch microphones. The microphones are inserted into the opposing holes at the ends of the phase calibrator and the diaphragms are exposed to the sound pressure produced by the built-in sound source. For accurate phase calibration at low frequencies, the microphones have to be of a type with extremely low sensitivity to sound pressures at their pressure-equalization channels, for example as with the GRAS 40AI Sound-intensity Microphone Pair. When these microphones are inserted into the sound-intensity coupler, only the diaphragms are exposed to the sound pressures generated by the sound source. The pressure equalization channels (usually at the back of the microphones) are not exposed to the same sound pressure as the diaphragms, and the influence of the pressure equalization channel on the phase characteristics of the microphones is therefore not measured. The GRAS 40AI sound-intensity microphone pair have specially designed venting systems which ensure extremely low sensitivity to sound pressures at the pressure-equalization vents within the operating frequency range.

The external generator is connected to the BNC connector on the side of the 51AB. For a sound pressure level of approximately 110 dB (re. 20 Pa) within the coupler and both microphones inserted, the generator should supply approximately 300 mVRMS.

# Specifications

**GRAS 51AB Phase Calibrator  
according to IEC 61043**

Page: 3

Frequency	Hz	50 to 6.3 k
Input signal, max.	Vrms	1
ANSI standard		S1.10
IEC standard		61043
Temperature range, operation	°C / °F	5 to 40 / 41 to 104
Weight	g / oz	515 / 18.166

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.

## Included

Two 1/4-inch microphone adapters

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.

# GRAS Worldwide

Subsidiaries and distributors in more than 40 countries

## HEAD OFFICE, DENMARK

**GRAS SOUND & VIBRATION**  
Skovlytoften 33  
2840 Holte  
Denmark  
Tel: +45 4566 4046  
[www.GRASacoustics.com](http://www.GRASacoustics.com)  
[gras@grasacoustics.com](mailto:gras@grasacoustics.com)

## USA

**GRAS SOUND & VIBRATION**  
9290 SW Nimbus Avenue  
Beaverton, OR 97008  
Tel: 503-627-0832  
Toll Free: 800-231-7350  
[www.GRASacoustics.com](http://www.GRASacoustics.com)  
[sales-usa@grasacoustics.com](mailto:sales-usa@grasacoustics.com)

## UK

**GRAS SOUND & VIBRATION**  
Unit 115, Gibson House,  
Ermine Business Park, Huntingdon,  
Cambridgeshire, PE29 6XU  
Tel: +44 (0) 7762 584 202  
[www.GRASacoustics.com](http://www.GRASacoustics.com)  
[sales-uk@grasacoustics.com](mailto:sales-uk@grasacoustics.com)

## CHINA

**GRAS SOUND & VIBRATION**  
Room 315, RuiBo Center(T1)  
Lane683, Shenhong Rd,  
Minhang District,  
Shanghai, China, 201107  
Tel: +86 21 64203370  
[www.GRASacoustics.cn](http://www.GRASacoustics.cn)  
[cnsales@grasacoustics.com](mailto:cnsales@grasacoustics.com)



## About GRAS Sound & Vibration

GRAS is a worldwide leader in the sound and vibration industry. We develop and manufacture state-of-the-art measurement microphones and related equipment for industries where acoustic measuring accuracy and repeatability are of the utmost importance. This includes applications and solutions for customers within the fields of aerospace, automotive, audiology, consumer electronics and other highly demanding industries. GRAS microphones are designed to live up to the high quality, durability and accuracy that our customers have come to expect, trust and require. GRAS Sound & Vibration is represented through subsidiaries and distributors in more than 40 countries and is part of Axiometrix Solutions, a leading test solutions provider comprised of globally recognized measurement brands. Read more at [www.grasacoustics.com](http://www.grasacoustics.com)

[grasacoustics.com](http://grasacoustics.com)

**GRAS**  
An Axiometrix Solutions Brand